



FLUID TRANSFER TECHNOLOGY

HAT3002 Hydraulic Torque Wrench Pump



Abdex Industries Pty. Ltd.
139 Wedgewood Road,
HALLAM, VIC. 3803 AUSTRALIA
Tel. +61 (3) 9796 3044
Fax. +61 (3) 9796 5964

Abdex Industries Pty. Ltd.
42 Bushland Ridge,
BIBRA LAKE, WA. 6163 AUSTRALIA
Tel. +61 (8) 9418 3044
Fax. +61 (8) 9418 42644

HAT3002 Specifications

Drive	Electric
Tank capacity	5.5L
Flow Rate (low-mid-high)	5.5-1.4-0.7 L/min
Output pressure	40 - 700bar
Power source	220/240V 50HZ
Motor	1.1KW
Weight	23KG
External dimensions	305x445x425mm

- Compact automatic three stage flow, for maximum efficiency.
- Induction motor for quiet operation and long life.
- Dual ports; run one or two wrenches simultaneously.
- ¼" NPT ports for industry compatibility
- Aluminum oil tank with oil level sight glass.
- 100mm diameter removable pressure gauge.
- Infinitely variable pressure adjustment between 40-700 bar.
- Fitted with oil cooler for continuous operation.
- Supplied with steel roll cage.