

HAZ3002 Air/Hydraulic Torque Wrench Pump



LARZEP AUSTRALIA PTY. LTD.
27 Metcalf Street,
DANDENONG SOUTH, VIC. 3175
Tel. +61 (3) 9796 3744
Fax. +61 (3) 9796 5964
e-mail: sales@larzep.com.au
www.larzep.com.au

LARZEP AUSTRALIA PTY. LTD.
42 Bushland Ridge,
BIBRA LAKE, WA. 6163 AUSTRALIA
Tel. +61 (8) 9418 4988
Fax. +61 (8) 9418 42644
e-mail: sales@larzep.com.au
www.larzep.com.au

HAZ3002 Specifications

Drive	Air/Hydraulic
Tank capacity	5.5L
Flow Rate (low-mid-high)	8.6-2.2-1.1 L/min
Output pressure	40 - 700bar
Power source	Air, 4-8 bar
Motor	Rotary, air driven
Weight	22KG
External dimensions	442 x 282 x 377mm

- Compact automatic three stage flow, for maximum efficiency.
- Air motor for hazardous environments.
- Dual ports; run one or two wrenches simultaneously.
- ¼" NPT ports for industry compatibility
- Aluminium oil tank with oil level gauge.
- 100mm diameter removable pressure gauge.
- Infinitely variable pressure adjustment between 40-700 bar.
- Fitted with air/oil cooler for constant operation.
- Supplied with steel roll cage.